

UV RESISTANT
BUILT FOR HARSH AUSTRALIAN CONDITIONS

NON-CONDUCTIVE
SAFE FOR ELECTRICAL WORK

FIBREGLASS SINGLE SCAFFOLD LADDERS

150KG RATED | AS 1892
LENGTHS 2.4m - 6.0m



LIGHTWEIGHT

Channel section, side rail, large flat top 'D' aluminium rung

STRENGTH

Swagelock 'D' Aluminium rung connection **stronger**
UV RESISTANT FIBREGLASS - lasts longer and better value

STABILITY & RIGIDITY

Rung braces to **increase stability** and **rigidity**

SOLID FOUNDATION

Large solid base feet - **plated for extra support**

| CODE | LENGTH (m) | WIDTH (mm) | WEIGHT (kg) | TRANSPORT CUBE (m³) |
|--------|------------|------------|-------------|---------------------|
| FSI082 | 2.4 | 365 | 8 | 0.08 |
| FSI102 | 3.0 | 365 | 9 | 0.09 |
| FSI122 | 3.6 | 365 | 10 | 0.11 |
| FSI142 | 4.2 | 365 | 12 | 0.13 |
| FSI162 | 4.8 | 365 | 14 | 0.15 |
| FSI182 | 5.4 | 365 | 16 | 0.17 |
| FSI202 | 6.0 | 365 | 18 | 0.19 |

All measurements are nominal and do not indicate 'exact weights and measures'



PROUDLY AUSTRALIAN MADE

LADaMAX®

AUSTRALIA'S LADDER SPECIALIST

www.ladamax.com.au

admin@ladamax.com.au

07 3205 7698